

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
9 September 2005 (09.09.2005)

PCT

(10) International Publication Number  
**WO 2005/083851 A2**

(51) International Patent Classification<sup>7</sup>: **H01S**

(21) International Application Number:  
PCT/GB2005/000678

(22) International Filing Date: 23 February 2005 (23.02.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
0403955.8 23 February 2004 (23.02.2004) GB  
0424271.5 2 November 2004 (02.11.2004) GB

(71) Applicant (for all designated States except US): **POWERLASE LTD** [GB/GB]; Imperial House, Link 10, Napier Way, Crawley, West Sussex RM10 9RA (GB).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **MASON, Michael** [GB/GB]; Powerlase Ltd, Imperial House, Link 10, Napier Way, Crawley, West Sussex RH10 9RA (GB). **PARSONS-KARAVASSILIS, Duncan** [GB/GB]; Powerlase Ltd, Imperial House, Link 10, Napier Way, Crawley, West Sussex RH10 9RA (GB). **HAY, Nicolas** [GB/GB]; Powerlase Ltd, Imperial House, Link 10, Napier Way, Crawley, West Sussex RH10 9RA (GB). **MATTHEW, Kelly** [GB/GB]; Powerlase Ltd, Imperial House, Link 10, Napier Way, Crawley, West Sussex RH10 9RA (GB). **COMLEY, Andrew** [GB/GB]; Powerlase Ltd, Imperial House, Link 10, Napier Way, Crawley, West Sussex RH10 9RA (GB). **CUMBERLAND, Burly** [GB/GB]; Powerlase Ltd, Imperial House, Link 10, Napier Way, Crawley, West Sussex RH10 9RA

(GB). **POULTER, Michael** [GB/GB]; Powerlase Ltd, Imperial House, Link 10, Napier Way, Crawley, West Sussex RH10 9RA (GB).

(74) Agent: **KILBURN & STRODE**; 20 Red Lion Street, London WC1R 4PJ (GB).

(81) Designated States (unless otherwise indicated, for every kind of regional protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

**Published:**

— without international search report and to be republished upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: A LASER APPARATUS



(57) Abstract: In a first embodiment, the invention makes use of a Neodymium doped YAG (Nd:Y.A.G) gain medium (202) placed in an, optical resonant cavity (2.00) formed by two mirrors (214, 216). Power extraction is maximised for a specific laser cavity. In particular the concave curvature on the rod ends contributes a negative lensing component to modify the strength of the thermal lens. In a second embodiment the present invention uses an amplifier rod medium with curved ends to act as lensing elements to collect emission from laser gain medium and or oscillator described in the first embodiment of the invention. The combination of thermal lens and curved rod ends produces a lensing effect which allows light to be directly coupled from a laser. In addition, variation of the input pump power allows for control of the thermal lens formed within the amplifier rod.

WO 2005/083851 A2